

Product Specification

Sodium Thiocyanate 50%

Chemical Name:	Sodium thiocyanate
Molecular Formula:	NaSCN
Molecular Mass:	81,1 g/mol
CAS-No.:	540-72-7
EC-No.:	208-754-4

Properties

Miscibility with water:	any desired ratio
-------------------------	-------------------

Specification

Appearance:	liquid
Content:	49 – 51 %
Iron:	max. 1 mg/kg
pH (as is):	6,0 – 10,0
Sulphides:	max. 80 mg/kg
Ammonia (as NH ₃):	max. 300 mg/kg
Color (APHA):	max. 40
Density (20/4°C):	1,289 – 1,309 g/ml

Typical Characteristics

Heavy metals:	< 10 mg/kg
---------------	------------

Analytical methods are available on request.

Major Applications

- In the fiber industry in spinning baths for acrylic fibers.
- In the water treatment industry as corrosion inhibitor.
- In agriculture as an intermediate in the manufacture of pesticides.
- In the photographic industry as sensitizer and stabilizer.
- In construction industry as a concrete hardening accelerator.

Storage

Store in a cool and dry place and avoid any contact to a strong acid. Use resistant equipment like polymer materials and high grade alloys. Iron corrosion can result in red coloration of product when exposed to UV-light. Although the product is stable when stored under ambient conditions without exposure to other chemicals, it is advised to re-analyze before use after 3 years of storage.

Packing and Transport

Sodium thiocyanate 50 % is delivered in:	Rail tank cars Road tankers 1000 l Containers
--	---

Hazard Identification No.:	none
UN-No.:	none

Safety advice

For transport, handling and first aid instructions we refer to our Material Safety Data Sheet (MSDS).

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability including for patent infringement, incurred in connection with the use of this product, data and suggestions.