

Product Specification

Ammonium Thiocyanate 55%

Chemical Name: Ammonium thiocyanate

Molecular Formula: NH₄SCN
Molecular Mass: 76,1 g/mol
CAS-No.: 1762-95-4
EC-No.: 217-175-6

Properties

Miscibility with water: any desired ratio

Specification

Appearance: liquid

Density (20/4°C): 1,125 – 1,135 g/ml

Typical Characteristics

Heavy metals: < 10 mg/kg

Analytical methods are available on request.

Major Applications

In the water treatment industry as corrosion inhibitor.

In the textile industry as adjuvant.

In agriculture as herbicide or as an intermediate in the manufacture of pesticides.

In the photographic industry as stabilizer and sensitizer.

In metal plating as an brightener for copper baths.

In metallurgy for the extraction of zirconium, hafnium, thorium and other rare earths.

Storage

Store in a cool and dry place and avoid any contact to a strong acid or a strong alkaline. Use resistant equipment like polymer materials and high grade alloys. Iron corrosion can result in red coloration of product when exposed to UV-light. Although the product is stable when stored under ambient conditions without exposure to other chemicals, it is advised to reanalyze before use after 3 years of storage.

Packing and Transport

Ammonium thiocyanate 50% is delivered in: Rail tank cars

Road tankers 1000 I Containers

Hazard Identification No.: none UN-No.: none

Safety advice

For transport, handling and first aid instructions we refer to our Material Safety Data Sheet (MSDS).

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability including for patent infringement, incurred in connection with the use of this product, data and suggestions.

Carbosulf Chem. Werke GmbH Geestemünder Str. 26 50735 Cologne Germany T +49-221-7496-101 F +49-221-7496-190

https://sulfurderivatives.nouryon.com/